


Camel-2000-SP1.0 潜伏移动机器人



Functional Features:

- **Positioning & Navigation:** Utilizes multi-sensor fusion navigation technologies, such as QR code navigation and Laser SLAM, to achieve high-precision positioning;
- **Motion Control:** Features omnidirectional drive, supporting multiple motion modes including forward, backward, lateral movement, and rotation
- **Power Management:** Supports multi-level battery threshold control; users can freely set the minimum charging threshold. It also supports idle-time charging control;
- **Safety Protection:** Supports multiple safety measures, including front/rear dual-laser obstacle avoidance, contact-based safety edge collision detection, emergency stop buttons, and ultrasonic sensors;
- **Human-Machine Interaction:** Features a touch screen and audiovisual alarms to indicate the real-time operating status of the equipment;
- **Control Modes:** Supports automatic, manual and remote control modes;
- **Material Handling:** Supports lifting and transport operations for goods with a rated load of 2000kg; provides customized load attachments to adapt to various application scenarios;
- **Network Communication:** Supports Wi-Fi communication with seamless roaming, as well as 5G network expansion;

Target Industries:

E-commerce, 3C Electronics, Tobacco, Pharmaceuticals, and more. It also serves as an expandable platform with customizable attachments to meet the needs of diverse application scenarios.

QR Code Spacing:

Standard reference spacing is 1000 x 1000 mm; supports non-uniform (irregular) QR code layout patterns.

Technical Specifications

Model			Camel-2000-SP1.0	
Basic Specifications	Dimensions: L*W*H		1530*1150*350 (±5)	mm
	Minimum Rotation Diameter		1704	mm
	Self-weight		350	Kg
	Rated Payload		2000	Kg
	Ground Clearance		25	mm
	Lifting Platform Dimensions		1420*1050	mm
	Human-Machine Interaction Methods		Touch Screen (5in)	Optional
	Lifting Drive		Hydraulic	/
	Lifting Height		100	mm
Motion Performance	Rated Speed (Unloaded)		1.5	m/s
	Rated Speed (Full Load)		1.2	m/s
	Acceleration (Unloaded)		0.6	m/s ²
	Acceleration (Full Load)		0.3	m/s ²
	Rotation Speed (Unloaded)		60	° /s
	Rotation Speed (Full Load)		30	° /s
	Drive Type		Differential Drive	/
Positioning & Navigation	Navigation Method		Laser SLAM or QR Code	/
	Stopping Accuracy		±10	mm
	Stop Angle Accuracy		±1	°
Battery	Battery Type		Lithium Iron Phosphate	
	Capacity / Rated Voltage		50/48	Ah/V
	Cycle Count		1500 cycles (100% DOD)	
	Battery Runtime (Rated Conditions)		6-8	h
	Charging Time		≤1.5	h
Safety & Protection	Frontal Safety Scanning	Mounting Height	238	mm
		Scanning Angle	250	°
	Rearward Safety Scanning	Mounting Height	238	mm


	Scanning Angle	230	°
	3D Visual Obstacle Avoidance	Optional	/
	Emergency Stop Button	Qty: 2 Front 2 Rear	/
	Contact-based Protection	Piezoelectric Safety Edge	/
	Audio-Visual Alarm	Classic	/
Trafficability	Chassis Suspension System	Dual-stage Floating Chassis	/
	Gradeability	$\leq 5\%/3^\circ$	%/°
	Step-climbing Ability	≤ 5	mm
	Gap-crossing Ability	≤ 30	mm

- ✧ The positioning accuracy specified above is obtained under ideal conditions;
- ✧ Actual accuracy is subject to site environment, rack/carrier dimensions, docking conditions, and other factors; please refer to the actual performance achieved on-site


Operating Environment Requirements

Environment	Indoor Environment
Floor Conditions	Optimal floor materials for AGV operation are hard concrete or conductive plastic (ESD) flooring
	The AGV operating surface must be kept free of iron filings, oil stains, and corrosive liquids
	Avoid seams in the driving path; maximum gaps should not exceed 10 mm
	Floor slope should not exceed 3° ; at docking positions requiring high-precision positioning, the slope must not exceed 1° ;
	To meet the requirements for safe braking distance and positioning accuracy, the floor's sliding friction coefficient must be at least 0.5;
Temperature	Working Environment Temperature: - Operating Temperature Range: -10°C to 40°C -Charging Temperature Range: 0°C to 40°C -Customization is required for cold storage environments
Ambient Humidity	Relative Humidity: 10%-90% (Non-condensing)
Signal	Dual-band WiFi (2.4GHz/5GHz) Wireless signal coverage strength $> -70\text{ dBm}$

Outline Dimensions Drawing



Charging Pile Docking



Optional Components

Components	Series	Description
Charging Station	Eh-4850-C1-130-0	
Manual Charger	Eh-4810-C1-S	
Slope	MR607X-7(L 216cm*W 84.5cm)	
Maintenance Tools	WDT-V1.0	