

Camel-600-SP2.1 潜伏移动机器人



Functional Features:

- Positioning & Navigation: Utilizes hybrid navigation technologies, such as QR code and Laser SLAM, to achieve high-precision positioning;
- Motion Control: Employs dual-wheel differential drive, supporting versatile motion control modes including forward, backward, and in-place rotation;
- Power Management: Supports multi-level battery threshold control with customizable minimum charging levels and idle-time charging management;
- Safety Protection: Supports multiple safety measures, including dual front/rear LiDAR, contact-based edge collision detection, and emergency top buttons;
- Human-Machine Interaction: Equipped with a touch screen and audiovisual alarms to indicate the current operation status of the equipment;
- Control Modes: Supports automatic, manual, and remote control operations;
- Material Handling: Supports lifting, transporting, and rotating payloads up to 600kg. Customizable load-handling attachments are available to adapt to diverse application scenarios;
- Network Communication: Supports Wi-Fi with seamless roaming and is expandable to 5G network connectivity;

Target Industries:

E-commerce, 3C Electronics, Tobacco, Pharmaceuticals, and more. It also serves as an expandable platform with customizable attachments to meet the needs of diverse application scenarios.

QR Code Spacing:

Standard reference spacing is 1000 x 1000 mm; supports non-uniform (irregular) QR code layout patterns.

Technical Specifications

Model		Camel-600-SP2.1	
Basic Specifications	Dimensions: L*W*H	950*650*255 (±5mm)	mm
	Minimum Rotation Diameter	963	mm
	Self-weight	130	Kg
	Rated Payload	600	Kg
	Ground Clearance	25	mm
	Lifting Platform Dimensions	850*600	mm
	Human-Machine Interaction Methods	Touch Screen (4.3in)	
	Lifting Drive	Electric	
	Lifting Height	60	mm
Motion Performance	Rated Speed (Unloaded)	1.9	m/s
	Rated Speed (Full Load)	1.5	m/s
	Acceleration (Unloaded)	0.6	m/s ²
	Acceleration (Full Load)	0.3	m/s ²
	Rotation Speed (Unloaded)	200	° /s
	Rotation Speed (Full Load)	100	° /s
	Drive Type	Differential Drive	/
Positioning & Navigation	Navigation Method	Laser SLAM or QR Code	/
	Lidar Mounting Height	201.5	mm
	Stopping Accuracy	±10	mm
	Stop Angle Accuracy	±1	°
Battery	Battery Type	Lithium Iron Phosphate	/
	Capacity / Rated Voltage	24/48	Ah/V
	Cycle Count	1500 cycles (100% DOD)	
	Battery Runtime (Rated Conditions)	8	h
	Charging Time	≤1.5	h
Safety & Protection	Frontal Safety Scanning	Mounting Height	201.5 mm
		Scanning Angle	250 °


	Rearward Safety Scanning	Mounting Height	202	mm
		Scanning Angle	180	°
	3D Visual Obstacle Avoidance		Optional	/
	Emergency Stop Button		Qty: 2 (Front & Rear x1)	/
	Contact-based Protection		Piezoelectric Safety Edge	/
	Audio-Visual Alarm		Classic	/
Trafficability	Chassis Suspension System		Dual-stage Floating Chassis	/
	Gradeability		$\leq 5\%/3^\circ$	%/°
	Step-climbing Ability		≤ 5	mm
	Gap-crossing Ability		≤ 30	mm

- ✧ The positioning accuracy specified above is obtained under ideal conditions ;
- ✧ Actual accuracy is subject to site environment, rack/carrier dimensions, docking conditions, and other factors; please refer to the actual performance achieved on-site


Operating Environment Requirements

Environment	Indoor Environment
Floor Conditions	Optimal floor materials for AGV operation are hard concrete or conductive plastic (ESD) flooring
	The AGV operating surface must be kept free of iron filings, oil stains, and corrosive liquids
	Avoid seams in the driving path; maximum gaps should not exceed 10 mm
	Floor slope should not exceed 3° ; at docking positions requiring high-precision positioning, the slope must not exceed 1° ;
	To meet the requirements for safe braking distance and positioning accuracy, the floor's sliding friction coefficient must be at least 0.5;
Temperature	Working Environment Temperature: -Operating Temperature Range: -10°C to 40°C -Charging Temperature Range: 0°C to 40°C -Customization is required for cold storage environments
Ambient Humidity	Relative Humidity: 10%-90% (Non-condensing)
Signal	Dual-band WiFi (2.4GHz/5GHz) Wireless signal coverage strength $> -70\text{ dBm}$

Outline Dimensions Drawing



Charging Pile Docking



Optional Components

Components	Series	Description
Charging Station	Eh-4850-C1-0	
Manual Charger	Eh-4810-C1-S	
Slope	MR607X-7(L 216cm*W 84.5cm)	
Maintenance Tools	WDT-V1.0	